



www.grandstream.com



OFFICE LOCATIONS

NORTH AMERICA

Corporate Headquarters
126 Brookline Ave, 3rd Floor
Boston, MA 02215
Voice: +1 617-566-9300
Fax: +1 617-249-1987

California
1208 John Reed Court
City of Industry, CA 91745
Voice: +1 626-638-9172
Fax: +1 617-249-1987

Dallas
2301 W. Plano Pkwy, Suite 208
Plano, TX 75075
Voice: +1 469-241-0100
Fax: +1 617-249-1987

ASIA

Shenzhen, China
Hangzhou, China
Kuala Lumpur, Malaysia

EUROPE, MIDDLE EAST & AFRICA

Casablanca, Morocco

LATIN AMERICA

Valencia, Venezuela

SIP Intercom

GSC3510

SIP Intercom Speaker/Microphone


High-fidelity 8W speaker, 3 directional mics, advanced acoustic echo cancellation, Bluetooth, dual-band WiFi, 1x 10/100 MBps ports, PoE/PoE+, 2-pin multi-purpose input, Full-band and wide-band codec support



GSC3505

1-Way Public Address SIP Speaker

High-fidelity 8W speaker, Bluetooth, dual-band WiFi, 1x 10/100 MBps ports, PoE/PoE+, Full-band and wide-band codec support



WiFi Access Points & Routers

GWN7630



4x4:4 MIMO, 200+ clients, 2.33 GBps, 175 meter range

GWN7610




3x3:3 MIMO, 250+ clients, 1.75 GBps, 175 meter range

GWN7600



2x2:2 MIMO, 450+ clients, 1.27 GBps, 165 meter range

GWN7600LR



Weatherproof casing, 2x2:2 MIMO, 450+ clients, 1.27 GBps, 300 meter range

GWN7000

Multi-WAN Gigabit Router

7 Gigabit ports (2 WAN, 5 LAN), Hardware accelerated VPNs, Embedded controller, 10 GBps, load balancing, & failover, firewall



Extension Modules

GBX20



Backlit LCD, 40 BLF/speed dial keys per module, works with GRP2615 and GXV3350

GXP2200 EXT



Backlit LCD, 40 BLF/speed dial keys per module, supported by GXP2140, GXP2170 and GXV3240

ATAs and Gateways

HT812/814/818

Analog Telephone Adapters



2/4/8 FXS ports, 2 SIP profiles, 2 Gigabit network ports with NAT router, auto-provisioning

HT813

Analog Telephone Adapter



1 FXS port, 1 FXO port with lifeline support, 2 10/100Mbps ports, 2 SIP profiles,

HT801 / 802

Analog Telephone Adapter



1/2 FXS ports, 1 10/100Mbps port, 1/2 SIP profiles, auto provisioning

GXW4500 Series

Digital VoIP Gateways

1/2/4 E1/T1/J1 spans, supports 30,60, or 120 concurrent calls, Gigabit network port, TLS and SRTP security encryption



GXW4200 Series

High Density FXS Gateways

16/24/32/48 FXS ports, 1 Gigabit network port, 4 SIP server profiles per system, independent SIP account per port, 132x48 backlit display



GXW4100 Series

Mid-Density FXO/FXS Gateways

4/8 FXO ports, 2 SIP profiles, integrated NAT router



IP Surveillance

GXV3610_HD / _FHD

IP Camera



3.6mm lens, Infrared, IP66-certified weather-proof, PoE

GXV3674_FHD

IP Camera



Variable-focal lens (2.8mm-12mm), IP66-certified weatherproof, Infrared, PoE

GXV3500

Video Encoder/Decoder/PAS



1-channel IP video encoder/decoder/public address system device, H.264, PoE



Unified Communications Solutions

For Small, Medium and Large Businesses

Carrier Grade IP Phones

GRP2616



16 SIP accounts, Dual LCDs (4.3" + 2.4"), 48 VPKs, cloud provisioning & management (GDMS), carrier-grade security, WiFi, Bluetooth, swappable faceplate, 2x Gigabit ports, PoE

GRP2615



16 SIP accounts, 4.3" LCD, 40 VPKs, cloud provisioning & management (GDMS), carrier-grade security, WiFi, Bluetooth, swappable faceplate, 2x Gigabit ports, PoE

GRP2614



4 SIP accounts, Dual LCDs (2.8" + 2.4"), 40 VPKs, cloud provisioning & management (GDMS), carrier-grade security, WiFi, Bluetooth, swappable faceplate, 2x Gigabit ports, PoE

GRP2613



3 SIP accounts, 2.8" LCD, 24 VPKs, cloud provisioning & management (GDMS), carrier-grade security, HD voice, swappable faceplate, PoE, 2x 10/100 MBps ports, PoE

GRP2612/P/W



2 SIP accounts, 2.4" LCD, 16 VPKs, cloud provisioning & management (GDMS), carrier-grade security, HD voice, swappable faceplate, 2x 10/100 MBps ports, PoE (GRP2612P), WiFi (GRP2612W)

IP Video Phones for Android

GXV3380



16 lines, 16 SIP accounts, dual Gigabit ports, PoE, 8" touch screen, WiFi, Bluetooth, Android 7.X, 2 MP camera, 1080p HD video output

GXV3370



16 lines, 16 SIP accounts, dual Gigabit ports, PoE, 7" touch screen, WiFi, Bluetooth, Android 7.0, 1 MP camera, 720p HD video output

GXV3350



16 lines, 16 SIP accounts, dual Gigabit ports, PoE, 5" touch screen, WiFi, Bluetooth, Android 7.0, 1 MP camera, 720p HD video output

High-End IP Phones

GXP2170



12 lines, 6 SIP accounts, dual Gigabit ports, PoE, 48 VPKs, Bluetooth

GXP2160



6 lines, 6 SIP accounts, dual Gigabit ports, PoE, 24 BLF/speed dial keys, Bluetooth

GXP2140



4 lines, 4 SIP accounts, dual Gigabit ports, PoE, Bluetooth

GXP2135



8 lines, 4 SIP accounts, dual Gigabit ports, PoE, 32 VPKs, Bluetooth

GXP2130



3 lines, 3 SIP accounts, dual Gigabit ports PoE, 8 BLF/speed dial keys, Bluetooth

Mid-Range IP Phones

GXP1780 / 1782



8 lines, 4 SIP accounts, dual Gigabit ports (1782), PoE, 32 digital BLF/speed dial keys

GXP1760 / 1760W



6 lines, 3 SIP accounts, PoE, 24 digital BLF/speed dial keys, WiFi (GXP1760W)

Basic IP Phones

GXP1630



3 lines/SIP accounts, dual Gigabit ports, PoE, 8 BLF/speed dial keys

GXP1628



2 lines/SIP accounts, dual Gigabit ports, PoE, 8 BLF/speed dial keys

GXP1620/1625



2 lines/SIP accounts, dual 10/100Mbps ports, PoE (GXP1625)

GXP1610/1615



2 lines, 1 SIP account, dual 10/100Mbps ports, PoE (GXP1615)

Mobility IP Phones

WP820

Enterprise Portable WiFi Phone



2 lines, 2 SIP accounts, dual-band WiFi, Bluetooth, HD voice, rechargeable battery, 7.5 hour talk time, push-to-talk

DP752/DP750

DECT Base Stations



High-end and mid-tier DECT base stations support any current DP device, up to 400m range outdoors and 50m range indoors

DP760

Wideband DECT repeater



Pairs with DP752/DP750 to extend range an additional 300m outdoors and 50m indoors

DP730/DP722/DP720

DECT Cordless HD IP Phones



10 line / 10 SIP account DECT handsets, HD voice, color-screens, over-the-air software/firmware updates, push-to-talk

IP PBXs

UCM6200 Series

IP PBX



UCM6202/6204: Up to 500 users, 50/75 concurrent calls, 2/4 FXO ports, 2 FXS ports, auto-provisioning, CDR

UCM6208: Up to 800 users, 100 concurrent calls, 8 FXO ports, 2 FXS ports, auto provisioning, CDR

UCM6510

IP PBX



Up to 2000 users, 200 concurrent calls, E1/T1/J1, 2 FXS ports, auto provisioning, CDR, pair 2 UCM6510s with an HA100 for a high-availability solution

HA100

High Availability Controller for the UCM6510



Interfaces Back Panel:
2 FXS A, 2 FXS B, 2 FXO A, 2 FXO B, 1 T1/E1 A, 1 T1/E1 B, 2 LAN/ 2 WAN

Interfaces Front Panel:
2 FXS ports, 2 FXO ports, 1 T1/E1, 1 LAN/1 WAN, 1 RS-485 for Primary UCM6510, 1 RS-485 for Secondary UCM6510

Video & Audio Conferencing

GVC3200/3202

Video Conferencing System



Supports Android, SIP and H.323 platforms, built-in MCU for 9/3-way video, 3/2 HDMI outputs, screen-sharing, Bluetooth, WiFi (GVC3200 only)

GVC3210

Video Conferencing Endpoint



Supports Android, SIP and H.323 platforms, 4k video resolution, 2 HDMI outputs, Miracast screen-sharing, Bluetooth, WiFi

IPVT10

Enterprise Video Conferencing Server



On-premise collaboration server, up to 300 participants, 10 simultaneous sessions, 120 video feeds per session, built-in recording & reports, advanced meeting control & scheduling, support for PC/Mac/mobile & SIP devices/PSTN trunk

GAC2500

HD IP Conference Phone



Android based, 6 lines, 4.3" color screen, 7-way conference bridge, Gigabit LAN port, PoE, integrated WiFi & Bluetooth

Facility Access Systems

GDS3710

HD IP Video Door System



Built-in hemispheric camera for 180° view 1080p video resolution, microphone and speaker for intercom functionality, Weatherproof/vandal-resistant metal casing, RFID chip reader, free management system, PoE

GDS3705

IP Audio Door System



Dual microphones and speaker for intercom functionality, Weatherproof/vandal-resistant metal casing, RFID chip reader, free management system, PoE